



Teknik Özellikler Technical Data	Motor (Vdc) Motor	Motor Gücü (W) Motor Power	Hız (cm/sec) Speed	Max.Kapı Genişliği (M) Max. Width of Gate	Max. Kapı Ağırlığı (kg) Max. Weight Of Gate
r-tec COUPER 24	24	80	1,3 - 1,6	2	125
r-tec LINEAR 400	24	50	1,3 - 1,6	3	300
r-tec PRINCE 400	24	120	1,6 - 2,0	3	200
r-tec PRINCE 600	24	120	1,6 - 2,0	4	400

KONTROL ÜNİTELERİ / CONTROL UNITS




G24 KONTROL ÜNİTESİ (24V)
G24 CONTROL UNIT (24V)



G220 KONTROL ÜNİTESİ (220V)
G220 CONTROL UNIT (220V)

AKSESUARLAR / ACCESSORIES



RF433 HARİCİ ALICI (230-24V)
RF433 EXTERNAL RECEIVERS (230-24V)



ZAR4 KUMANDA (4 KANAL)
ZAR4 REMOTE CONTROLS (4 Ch.)



MF FOTOŞEL
MF PHOTOCCELL



BT180 PİLLİ FOTOŞEL
BT180 PHOTOCCELL WITH BATTERY



A-FLA LED FLAŞÖR (230-24V)
A-FLA LED FLASHING LIGHT (230-24V)



HARİCİ ANTEN
EXTERNAL ANTENNA




LOOP DEDEKTÖR 1 KANAL
LOOP DETECTOR 1 Ch.



AKÜ KİT
BATTERY KIT



ELEKTRİKLİ KİLİT VAZAY (12V)
HORIZONTAL ELECTRIC LOCK (12V)



ELEKTRİKLİ KİLİT DÜŞEY (12V)
VERTICAL ELECTRIC LOCK (12V)



Geleceğe Açılan Kapılar...
The doors that OPEN to the future...

Dinamix & DinamixBAR



Dinamix

DinamixBAR

DinamixBAR L

Teknik Özellikler Technical Data	Enerji Girişi (Vac) Power Supply	Motor (Vdc) Motor	Motor Gücü (W) Motor Power	Açma Süresi (sec) Opening Time	Kol (m) Bar
r-tec Dinamix 4000 DinamixBar 4000	230	24	190	4	4
r-tec Dinamix 5000 DinamixBar 5000	230	24	190	5	5
r-tec Dinamix 6000 DinamixBar 6000	230	24	190	6 - 8	6
r-tec Dinamix 7000 DinamixBar 7000	230	24	190	6 - 8	7
r-tec DinamixBar L9000	230	24	190	6 - 9	9

KONTROL ÜNİTELERİ / CONTROL UNITS



AKSESUARLAR / ACCESSORIES

- G24 KONTROL KARTI (24V)
G24 CONTROL CARD (24V)
- R433 HARİCALICI (230-24V)
R433 EXTERNAL RECEIVERS (230-24V)
- ZAR4 KUMANDA (4 KANAL)
ZAR4 REMOTE CONTROLS (4 Chn.)
- MF FOTOSEL
MF PHOTOCCELL
- BT180 PİLLİ FOTOSEL
BT180 PHOTOCCELL WITH BATTERY
- A-FLA LED FİAŞÖR (230-24V)
A-FLA LED FLASHING LIGHT (230-24V)
- LOOP DEDEKTÖR 1 KANAL
LOOP DEDECTOR 1 Chn.
- AKÜ KİT
BATTERY KIT
- LED KİT
LED KIT
- BASTON ARIK
MOBILE STAND FOR BARS
- KOL KURUMA ARAÇI
JOINT FOR BARS
- SAÇAK (2M)
CURTAIN (2M)



KING Serisi



Teknik Özellikler Technical Data	Enerji Girişi (Vac) Power Supply	Motor (Vdc/Vac) Motor	Motor Gücü (Nm) Stall Torque	Max. Hız (cm/sec) Max. Speed	Max. Kapı Ağırlığı (kg) Max. Weight Of Gate
r-tec KING524F	230	24	2.95	53	500
r-tec KING1224F	230	24	4.15	44	1200
r-tec KING500	230	230	200	21	500
r-tec KING1000	230	230	400	21	1000
r-tec KING2000	230	230	400	21	2000
r-tec KING3000 FU	230	380	750	67	3000
r-tec KING4000	380	380	2200	21	4000

KONTROL ÜNİTELERİ / CONTROL UNITS



AKSESUARLAR / ACCESSORIES

